



# DARC 160GS

1P, DUAL VOLTAGE, POCKET TOOL

- SUITABLE FOR VARIABLE VOLTAGE ENVIRONMENT.



## Processes

- MMA

## Package Includes

- Inverter power source
- Electrode holder, 1.8m
- Earth clamp, 1.2m

## Optional Accessories

- Kit case
- Brush
- Helmet

## Features

- CPU built-in.
- VRD adjustable.
- Self-adaptive Arc force and Hot start built-in, Anti-sticking.
- Fan as needed, reduce noise and dust inside the machine.
- Non-stop welding for 2.5mm and 3.2mm electrode.
- Suitable for acid and basic electrode.



Model	Input Voltage/Phase/Frequency	Output Current/Voltage/Duty Cycle (40°C)	Amps Input At Rated Output	Output Range/ OCV	Dimension (mm)	Weight (kg)
ARC 160GS	110V/1P/50-60Hz 220V/1P/50-60Hz	*110V: 100A/22V/20% 50A/20V/100% *220V: 150A/24V/20% 60A/20.4V/100% *Standard : EN60974-6	110V: 35A@110A 220V: 29.1A@150A	110V: 40-100A/58V/17V(VRD) 220V: 40-150A/58V/17V(VRD)	335*123*220	4.8